

| Model | | EB0625 | EB1000 | EB1250 | EB2000 | EB2500 | EB3200 | |
|---|------|--------------------------|------------|------------|--------------------------|------------|--------------|--|
| Weight of Machine | Kg | 72 | 110 | 150 | 270 | 315 | 380 | |
| Nominal Capacity <i>(length x thickness)</i> | mm | 625 x 1.6 | 1000 x 1.6 | 1250 x 1.6 | 2000 x 1.6 | 2500 x 1.6 | 3200 x 1.2 | |
| Clamping Force | Tons | 3 | 4,5 | 6 | 9 | 12 | 10 | |
| Electricity Supply | | 1 phase, 220/240vac, 10A | | | 2 phase, 220/240vac, 15A | | | |
| Duty Cycle | % | 30 | | | | | | |
| Protection | °C | Thermal cut-out 70°C | | | | | | |
| Foot Switch | | No | | Optional | Standard | | | |
| Bending-edge Length | mm | 670 | 1050 | 1300 | 2090 | 2590 | 3290 | |
| Distance between Lifters | mm | 630 | 1010 | 1260 | 2028 | 2528 | 3228 | |
| U-Channel bends, minimum spacing | mm | 16*** | | | 19*** | | 45*** | |
| Closed channel, minimum internal | mm | 99 x 27*** | | | 114 x 22*** | | 114 x 45*** | |
| Z-reverse bends, minimum spacing | mm | 35** / 16* | | 36** / 18* | | | | |
| Thickness Capacities, full length <i>(material thickness can increase depending on the length of bend)</i> | | | | | | | | |
| ...Mild steel | mm | 1.6** / 1.2* | | | | | 1.2** / 1.0* | |
| ...Aluminium (medium-hard) | mm | 1.6** / 1.2* | | | | | 1.2** / 1.0* | |
| ...Copper, Zinc, Brass (medium-hard) | mm | 1.6** / 1.2* | | | | | 1.2** / 1.0* | |
| ...Stainless steel | mm | 1.0** / 0.9* | | | | | 0.9** / 0.8* | |
| *** with standard full length clamp bar **with bending beam extension bar *extension bar removed | | | | | | | | |